

## CLAIMS

1. A developer supply container detachably mountable to an image forming apparatus, said  
5 developer supply container comprising:
  - a container body for accommodating a developer, said container body being provided with a discharge opening for permitting discharging of the developer;
  - feeding means for feeding the developer in said  
10 container body toward said discharge opening; and
  - a driving source for driving said feeding means.
2. A toner supply container according to Claim 1, further comprising a starter, operable from said image  
15 forming apparatus, for starting said driving source.
3. A toner supply container according to Claim 1, wherein said driving source is a compressed gas storing in a storing portion.  
20
4. A toner supply container according to Claim 3, wherein an internal pressure of said storing portion is 10 - 150KPs.
- 25 5. A toner supply container according to Claim 3, wherein said feeding means includes a vibration member vibratable with releasing of the compressed gas.

6. A toner supply container according to Claim 3,  
wherein said feeding means includes a movable member  
movable toward said discharge opening with releasing  
5 of the compressed gas.

7. A toner supply container according to Claim 1,  
wherein said driving source includes an electric  
accumulator, and a driving motor driven by electric  
10 energy from said electric accumulator.

8. A developer supply container detachably  
mountable to an image forming apparatus, said  
developer supply container comprising:  
15 a container body for accommodating a developer,  
said container body being provided with a discharge  
opening for permitting discharging of the developer;  
a storing portion for storing compressed gas  
for feeding the developer in said container toward  
20 said discharge opening.

9. A toner supply container according to Claim 8,  
further comprising a mechanism, operable from said  
image forming apparatus, for releasing the compressed  
25 gas into said container.

10. A toner supply container according to Claim 8,

wherein an internal pressure of said storing portion  
is 10 - 150KPs.